

DERWENT-ACC-NO: 1981-H3898D

DERWENT-WEEK: 198132

COPYRIGHT 2007 DERWENT INFORMATION LTD

TITLE: Synchronising circuit digital matched filter - has input
signal train clocked into shift register and
pseudo-random signal shifted on switching out register
feedback loop

INVENTOR: ZAVODII, E S

PATENT-ASSIGNEE: PODLINNOV A D[PODLI]

PRIORITY-DATA: 1978SU-2659027 (August 18, 1978)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
SU 771891 B	October 20, 1980	N/A	003	N/A

INT-CL (IPC): H04B003/40

ABSTRACTED-PUB-NO: SU 771891B

BASIC-ABSTRACT:

The digital matched filter is used in radio communications synchronising circuits. It operates in three stages: (i) recording the input signal train symbol into a shift register; (ii) comparison of the current code signal state of shift register (2) with a reference signal train of generator (4); and (iii) setting the scan time for the window of the pseudo-random signal train component.

At the first stage, at each clock pulse from generator (1), the binary symbol ('1' or '0') of the input signal train is read into the shift register (2) and shifts the pseudo-random signal train on switching out the feedback loop of register (2). The second stage begins with the start-up of the processing stage (8). Bul.38/15.10.80.

CHOSEN-DRAWING: Dwg.1

TITLE-TERMS: SYNCHRONISATION CIRCUIT DIGITAL MATCH FILTER INPUT SIGNAL
TRAIN

CLOCK SHIFT REGISTER PSEUDO RANDOM SIGNAL SHIFT SWITCH REGISTER
FEEDBACK LOOP

DERWENT-CLASS: W02

EPI-CODES: W02-C01X;